







Descriptif technique :

Robuste et économe en énergie, le CARN est idéal pour l'éclairage des salles machine de moyenne et grande taille ou des coursives. Fixation arrière par vis extérieures au bâti (fournies). Matière: PC et ABS classés UL94 V0 certifiant la non inflammabilité des matériaux. Fourni avec 2 presse-étoupes. Disponible avec éclairage de secours blanc neutre 24 VDC et presse-étoupe supplémentaire (01727, 01728, 01729, 01730, 01731, 01732). Supporte les températures de -25°C à +80°C.

Description :

Its very low consumption and robustness make CARN the perfect light for the medium and large engine rooms and gangways. Fitting by 2 holes outside the light body (screws supplied). Made in PC and ABS UL94 V0 very low flammability classified. Supplied with 2 cable glands. Available with emergency lighting in 24 VDC with additional cable gland (01727, 01728, 01729, 01730, 01731, 01732). Withstands temperatures from -25°C to +80°C

	Alim. Voltage	Hertz Hertz	Description Description	Puissance Power	Couleur Colour	Matériau Material	Poids Weight	Angle Angle	Conso. Cons.	Réf. Ref.
4500 K	24-30 VDC	-	Plafonnier 36 W 36 W Downlight	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	23 W	01589
4500 K	24-30 VDC	-	Plafonnier 36 W avec secours 36 W Downlight with backup	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	23 W	01727
4500 K	225-260 VAC	50Hz	Plafonnier 36 W 36 W Downlight	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	18 W	01590
4500 K	225-260 VAC	50Hz	Plafonnier 36 W avec secours 36 W Downlight with backup	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	18 W	01728
4500 K	225-260 VAC	60Hz	Plafonnier 36 W 36 W Downlight	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	18 W	01678
4500 K	225-260 VAC	60Hz	Plafonnier 36 W avec secours 36 W Downlight with backup	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	18 W	01731
3000 K	225-260 VAC	50Hz	Plafonnier 36 W 36 W Downlight	3000 lm	3000 K Blanc chaud 3000 K Warm white	PC+ ABS PC & ABS	890 g	120°	18 W	01675
3000 K	225-260 VAC	50Hz	Plafonnier 36 W avec secours 36 W Downlight with backup	3000 lm	3000 K Blanc chaud 3000 K Warm white	PC+ ABS PC & ABS	890 g	120°	18 W	01730
3000 K	225-260 VAC	60Hz	Plafonnier 36 W (60 Hz) 36 W (60 Hz) Downlight	3000 lm	3000 K Blanc chaud 3000 K Warm white	PC+ ABS PC & ABS	890 g	120°	18 W	01679
3000 K	225-260 VAC	60Hz	Plafonnier 36 W (60 Hz) avec secours 36 W (60 Hz) Downlight with backup	3000 lm	3000 K Blanc chaud 3000 K Warm white	PC+ ABS PC & ABS	890 g	120°	18 W	01732
4500 K	110-230 VAC	50/60 Hz	Plafonnier Dimmable 36 W (50/60 Hz) 36 W (50/60 Hz) Dimmable Downlight	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	18 W	01671
4500 K	110-230 VAC	50/60 Hz	Plafonnier Dimmable 36 W (50/60 Hz) avec secours 36 W (50/60 Hz) Dimmable Downlight with backup	3000 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	890 g	120°	18 W	01729