
LED 7 W ≈ 11 W





Descriptif technique :

Forte puissance dans un faible encombrement, idéal pour l'éclairage des zones étroites. En version rouge et blanche, avec ou sans interrupteur, Kerguelen est idéale pour l'éclairage de votre passerelle. Fixation par 2 vis en face avant. Polarité électrique indifférente. Faible consommation électrique. Fixation en saillie. Livré avec 1m de fil électrique dénudé*.

*(sauf 1599,1603,01604 et 01605)

Description:

High power for a slim waterproof appliance, ideal for narrow areas lighting. In its red & white version, with or without switch, Kerguelen is ideal to illuminate your bridge at night. Fastening by 2 screws. Reverse polarity protected. Low consumption External mounting. Supplied with 1m of electrical wire*.

*(except 01599,01603,01604,01605)

	Alimentation Power supply	Puiss. lumin. Lighting Pow.	Couleur Colour	Matériau Material	Poids Weight	Angle Angle	Conso. Cons.	Temp. Temp.	Réf. Ref.
4500 K	Sans inter. - Blanc White - No switch	10-30 VDC	800 lm	4500 K Blanc neutre Neutral White	Alu.+ PMMA Alu.& PMMA	450 g	120°	13,5 W	-20°C +55°C	01599
4500 K	Avec inter.- Blanc White With switch	10-30 VDC	800 lm	4500 K Blanc neutre Neutral White	Alu.+ PMMA Alu.& PMMA	450 g	120°	13,5 W	-20°C +55°C	01603
4500 K	Sans inter. - Blanc White - No switch	10-30 VDC	550 lm	4500 K Blanc neutre Neutral White	Alu.+ PMMA Alu.& PMMA	225 g	120°	9 W	-20°C +55°C	01604
4500 K	Avec inter.- Blanc White With switch	10-30 VDC	550 lm	4500 K Blanc neutre Neutral White	Alu.+ PMMA Alu.& PMMA	225 g	120°	9 W	-20°C +55°C	01605
4500 K	Sans inter. - Blanc White - No switch	24-30 VDC	800 lm	4500 K Blanc neutre Neutral White	Alu.+ PMMA Alu.& PMMA	715 g	120°	7 W	-20°C +55°C	01385
3100 K	Sans inter. - Blanc White - No switch	12 VDC	800 lm	3100 K Blanc chaud Warm White	Alu.+ PMMA Alu.& PMMA	715 g	120°	7 W	-20°C +55°C	01550
4500 K	Sans inter Blanc et rouge White & Red No switch	24-30 VDC	800 lm	4500 K Blanc neutre + Rouge Neutral White + Red	Alu.+ PMMA Alu& PMMA	715 g	120°	7 W	-20°C +55°C	01386
3100 K	Sans inter Blanc et rouge White & Red No switch	24-30 VDC	800 lm	3100 K Blanc chaud + Rouge Warm White + Red	Alu.+ PMMA Alu& PMMA	715 g	120°	7 W	-20°C +55°C	01443