
LED 22 W ≈ 28 W






Descriptif technique :

Robuste et économe en énergie, le KELLER est idéal pour l'éclairage des salles machine de moyenne taille. Fixation arrière par vis extérieures au bâti. Matière : PC et ABS classés UL94 V0 certifiant la non inflammabilité des matériaux. Fourni avec 2 presse-étoupe et 2 vis de fixation. Eclairage de secours 24 VDC ou 230 VAC disponible en option (avec presse-étoupe supplémentaire).

Description :

Robust and not greedy in energy, KELLER is ideal for the lighting of medium size engine rooms. Fitting by 2 holes outside the light body. Made in PC and ABS UL94 V0 very low flammability classified. Supplied with 2 cable glands and 2 mounting screws. Optional emergency lighting in 24 VDC or 230 VAC available (with additional cable gland).



	Alimentation Power supply	Puiss. lumineuse Lighting Power	Couleur Colour	Matériau Material	Poids Weight	Angle Beam angle	Conso. Cons.	Temp. Temp.	Références References
Plafonnier 22W 22W Downlight	225-260 VAC (50 Hz)	2000 lm	4500 K Blanc neutre Neutral white	PC+ ABS PC & ABS	625 g	120°	15W	-20°C +70°C	01357
Plafonnier 22W 22W Downlight	24-30 VDC	2000 lm	4500 K Blanc neutre Neutral white	PC+ ABS PC & ABS	625 g	120°	28W	-20°C +70°C	01358
Plafonnier Rouge Red Downlight	225-260 VAC (50 Hz)	1000 lm	Rouge / Red	PC+ ABS PC & ABS	625 g	120°	22W	-20°C +70°C	01359
Plafonnier Rouge Red Downlight	24-30 VDC	1000 lm	Rouge / Red	PC+ ABS PC & ABS	625 g	120°	22W	-20°C +70°C	01376
Option secours Emergency lighting	24-30 VDC	140 lm	4500 K Blanc neutre Neutral white				3 W	-20°C +70°C	01377
Option secours Emergency lighting	225-260 VAC	140 lm	4500 K Blanc neutre Neutral white				3 W	-20°C +70°C	01404



Photo: Plasti Pêche