

LED 22 W ≈ 36 W





Descriptif technique :

Avec son corps INOX 316L peint et ses ferrures inox, *SIECK* est notre plafonnier conçu pour l'éclairage extérieur ou sous ponts couverts. **Grâce à sa verrine blanche transparente, l'éclairage est uniforme et les points lumineux des leds sot masqués.** Fixation intérieure par 2 vis (non fournies). Matière : INOX 316L et PMMA blanc transparent. Fourni avec 2 presses-étoupe. Eclairage de secours 24 VDC ou 230 VAC disponible en option.

Description:

With its 316L Stainless Steel Body and fastenings, *SIECK* is ideal for the external area lighting of gangways or semi-open decks. **The transparent white cover provides a uniform lighting and hides the leds.** Fitting by 2 holes inside the light body (screws not supplied). Made in Stainless Steel and transparent white PMMA. Supplied with 2 cable glands. Optional backup lighting in 24 VDC or 230 VAC available.

	Alimentation Power supply	Puiss. lumineuse Lighting Power	Couleur Colour	Matériau Material	Poids Weight	Angle Beam angle	Conso. Cons.	Temp. Temp.	Réf. Ref.
Plafonnier INOX 36W 36W S/S Downlight	24-30 VDC	3000 lm	4500 K Blanc neutre Neutral white	INOX + PMMA Stainless Steel & PMMA	1900 g	120°	34 W	- 20°C + 70°C	01406
Plafonnier INOX 36W 36W S/S Downlight	225-260 VAC (50 Hz)	3000 lm	4500 K Blanc neutre Neutral white	INOX + PMMA Stainless Steel & PMMA	1900 g	120°	27 W	- 20°C + 70°C	01407
Option secours Emergency lighting	24-30 VDC	140 lm	4500 K Blanc neutre Neutral white				3.9 W	- 20°C + 70°C	01341
Option secours Emergency lighting	225-260 VAC	140 lm	4500 K Blanc neutre Neutral white				3.9 W	- 20°C + 70°C	01405

