

SIECK

PLAFONNIER LED ÉTANCHE / WATERPROOF LED DOWNLIGHT

LED 22 W ≈ 36 W





Descriptif technique :

Avec son corps INOX 316L peint et ses ferrures inox, *SIECK* est notre plafonnier conçu pour l'éclairage extérieur ou sous ponts couverts. **Grâce à sa verrine blanche transparente, l'éclairage est uniforme et les points lumineux des leds sot masqués.** Fixation intérieure par 2 vis (non fournies). Matière : INOX 316L et PMMA blanc transparent. Fourni avec 2 presses-étoupe. Eclairage de secours 24 VDC ou 230 VAC disponible en option.

Description:

With its 316L Stainless Steel Body and fastenings, *SIECK* is ideal for the external area lighting of gangways or semi-open decks. **The transparent white cover provides a uniform lighting and hides the leds.** Fitting by 2 holes inside the light body (screws not supplied). Made in Stainless Steel and transparent white PMMA. Supplied with 2 cable glands.

	Alimentation Power supply	Puiss. lumineuse Lighting Power	Couleur Colour	Matériau Material	Poids Weight	Angle Beam angle	Conso. Cons.	Temp. Temp.	Réf. Ref.
Plafonnier INOX 36W 36W S/S Downlight	24-30 VDC	3000 lm	4500 K Blanc neutre Neutral white	INOX + PMMA Stainless Steel & PMMA	1900 g	120°	34 W	- 20°C + 70°C	01406
Plafonnier INOX 36W 36W S/S Downlight	225-260 VAC	3000 lm	4500 K Blanc neutre Neutral white	INOX + PMMA Stainless Steel & PMMA	1900 g	120°	27 W	- 20°C + 70°C	01407
Option secours Emergency lighting	24-30 VDC	140 lm	4500 K Blanc neutre Neutral white				3.9 W	- 20°C + 70°C	01341
Option secours Emergency lighting	225-260 VAC	140 lm	4500 K Blanc neutre Neutral white				3.9 W	- 20°C + 70°C	01405