LED 29 W ≈ 400 W LED 90 W ≈ 1200 W

VHF AIS CEM CE IP67 IK09

## Descriptif technique :


Avec son **corps INOX 316L peint et ses ferrures inox, PONANT est notre projecteur conçu pour l'éclairage extérieur.** Contrairement aux projecteurs à 1 led centrale, il offre un faisceau de diffusion très large idéal pour éclairer sous un portique. Fixation par 3 vis (non fournies). Matière : INOX 316L et verre. Fourni avec 5 mètres de câble marin. Etanchéité du presse étoupe par gaine thermorétractable adhésivée.

## Description :


With its **Stainless Steel 316L Body and fastenings, PONANT is our floodlight ideal for the external area lighting.** Unlike floodlights with a central led, it offers a very wide beam, perfect to illuminate below a trawler gantry. Fitting by 3 screws (not supplied). Made in 316L Stainless Steel and glass. Supplied with 5 meters of marine cable. Sealing of the cable gland by adhesive Lined Heat Shrink Tubing.

Ref. 01381 & 01361 - PONANT 400 W








Ref. 01408 & 01409 - PONANT 1200 W








| Alimentation<br>Power supply | Puiss. lumineuse<br>Lighting Power | Couleur<br>Colour | Matériau<br>Material | Poids<br>Weight | Angle diffusion<br>Beam angle | Consommation<br>Consumption | Température<br>Temperature | Références<br>References |
|---|---|---|---|---|---|---|---|---|
| 24-30 VDC | 3000 lm | 6000 K Blanc froid<br>6000 K Cool white | Inox 316 L<br>S. S. 316 L | 3150 g | 120° | 34 W | - 20° /<br>+ 55°C | 01381 |
| 225-260 VAC | 3000 lm | 6000 K Blanc froid<br>6000 K Cool white | Inox 316 L<br>S. S. 316 L | 3150 g | 120° | 25 W | - 20° /<br>+ 55°C | 01361 |
| 24-30 VDC | 9000 lm | 6000 K Blanc froid<br>6000 K Cool white | Inox 316 L<br>S. S. 316 L | 6250 g | 120° | 90 W | - 20° /<br>+ 55°C | 01408 |
| 225-260 VAC | 9000 lm | 6000 K Blanc froid<br>6000 K Cool white | Inox 316 L<br>S. S. 316 L | 6250 g | 120° | 90 W | - 20° /<br>+ 55°C | 01409 |

Crédit photo Frédérique Huet