
LED 1,9 W ≈ 10 W  LED 2,4 W ≈ 20 W










LED 1,9 W ≈ 10 W

| | Alimentation Power supply | Puiss. lumineuse Lighting Power | Couleur Colour | Matériau Material | Poids Weight | Angle Beam angle | Conso. Consumption | Sans inter. No switch | Avec inter. With switch |
|---|---|---|---|---|---|---|---|---|---|
| Inox poli Polished S.S | 9-30 VDC | 140 lm | 3000 K Blanc chaud 3000 K Warm white | inox + ABS S/S + ABS | 54 g | 120° | 1,9 W | 01432 | 01433 |
| Inox brossé Brushed S.S | 9-30 VDC | 140 lm | 3000 K Blanc chaud 3000 K Warm white | inox + ABS S/S + ABS | 54 g | 120° | 1,9 W | 01525 | 01526 |
| Blanc White | 9-30 VDC | 140 lm | 3000 K Blanc chaud 3000 K Warm white | inox blanc white S/S | 54 g | 120° | 1,9 W | 01514 | 01515 |

LED 2,4 W ≈ 20 W

| | Alimentation Power supply | Puiss. lumineuse Lighting Power | Couleur Colour | Matériau Material | Poids Weight | Angle Beam angle | Conso. Consumption | Sans inter. No switch | Avec inter. With switch |
|---|---|---|---|---|---|---|---|---|---|
| Inox poli Polished S.S | 9-30 VDC | 250 lm | 3000K Blanc chaud 3000K Warm white | inox+ABS S/S + ABS | 54 g | 120° | 2,4 W | 01434 | 01435 |
| Inox brossé Brushed S.S | 9-30 VDC | 250 lm | 3000K Blanc chaud 3000K Warm white | inox+ABS S/S + ABS | 54 g | 120° | 2,4 W | 01527 | 01528 |
| Blanc White | 9-30 VDC | 250 lm | 3000K Blanc chaud 3000K Warm white | inox blanc white S/S | 54 g | 120° | 2,4 W | 01529 | 01530 |

## Descriptif technique :


**Spot de cabine en ABS et cache inox poli ou brossé ou blanc**. Diffusion large. Montage encastré aisé par 2 ressorts. Livré avec 10 cm de fil électrique dénudé. En version avec ou sans interrupteur, le spot est ETANCHE IP67.
01432, 01514 et 01525 sont dimmables avec gradateur Mantagua (Ref. 01159)
Peut être fourni avec joint isolant permettant un montage inox sur aluminium.



Support saillie (avec vis)
Surface mount holder (with screws)

## Description:

**Cabin spotlight made of ABS and mirror polished Stainless Steel or white**. Large beam. Easy recessed mounting with the 2 springs. Comes with 10 cm of electrical wire. In its with or without switch version, the spot is WATERPROOF IP67.
01432, 01514 and 01525 are dimmable with Mantagua dimmer (Ref. 01159). Can be supplied with plastic sealing allowing stainless steel mounting on aluminium base.



Dimensions : L 98 x l 98 x H 17 mm
Dimensions : L 98 x W 98 x H 17 mm

| | |
|---|---|
| Rehausse inox poli Polished stainless steel mounting holder | 01441 |
| Rehausse inox brossé Brushed stainless steel mounting holder | 01531 |
| Réhausse blanc White mounting holder | 01491 |